KSML92







desktop

panel mount

- •92 keys, short travel
- •50 mm IP68 trackball
- •IP67 sealing

# COMPACT LED BACKLIT KEYBOARD

This 92 key backlit keyboard features a compact full MF keyboard with integrated numpad and a large 50mm waterproof trackball with removable ball.

## MAIN FEATURES

- Compact layout
- •Removable 50 mm optical trackball
- •High brightness LED's with fibre optics
- •Illumination of the key legends and contour, the trackball contour and even customer logo's or trademarks
- •Low power LED's warrant for a long life
- •No external power supply necessary, keyboard port power sufficient
- •Dimmable backlighting at 8 levels by two dedicated keys
- •Intelligent luminosity setting of "numlock" and capslock" LED's
- •White backlighting as standard, other colours on request

### <u>Panel mount version</u>:

- $\bullet \ A luminium \ carrier \ and \ silicone \ sponge \ panel \ sealing$
- Front panel mounting with holes (for countersunk M4 screws, not included)
- •Added silicon sponge seal for perfect sealing into the user's panel
- •The rear side components are protected by a covering metal plate
- $\bullet$ Dimensions / weight : 385 x 185 x 50 mm / 1,2 kg

#### **Desktop version**:

- •The keyboard is mounted in a robust, all steel enclosure
- •Industrial epoxy coating (mid-grey).
- •Dimensions / weight: 418 x 246 x 70 mm / 3,5 kg

### **GENERAL TECHNICAL SPECIFICATIONS**

Sealing : IP67 sealed

Keys : 92 short travel switches, tactile feel switches

with 0,3 mm travel and 2,55 N operating force

Pointing Device : 50 mm optical trackball, epoxy resin ball

Output : 1,6 meter PS/2 or USB cable(s)
Power requirements : Directly from PS/2 or USB port

Operating temp. : 0°C to +60°C

Front layer : Black polyester front layer with embossed keys,

scratch and chemical resistant

#### CONNECTIVITY

The PS/2 keyboards are supplied with two 1,6 m long shielded straight cable ended with 6 pin mini DIN plugs. The USB versions are supplied with one 1,6m long shielded straight cable ended by a USB type A connector.

\* Due to the increasing differences of PS/2 mouse port specifications of the various PC manufacturers, we do recommend that this unit should be tested on the final PC configuration and operating system prior to installing it in series.

### **CUSTOMIZATION**

Possible customization includes adapted backlighting controls, addition of company logo or specific function keys, different layouts, different colour.






#### **ORDER INFO**


COUNTRY LAYOUT	PANEL MOUNT	DESKTOP
US Qwerty	KSML92F1xxx-WLED	KSML92S1xxx-WLED
Cyrillic Russian	KSML92F7xxx-WLED	KSML92S7xxx-WLED
German Qwertz	KSML92F49xxx-WLED	KSML92S49xxx-WLED


xxx = protocol output : USB or PS/2

White backlighting as standard, other colours on request










COLOURS

Keyboard & Key Background : PANTONE Black 2 C 2X Key edges & key legends : white Translucent









COLOURS

Keyboard & Key Background : PANTONE Black 2 C 2X Key edges & key legends : white Translucent



The company reserves the right to alter without prior knowledge the specification or design of any standard product or service.